

FITTING INSTRUCTIONS

(INCLUDING SPECIFIC OPERATING PRESSURES)

CR5035



- ⚠** This air suspension system is designed to assist the original vehicle manufacturer's suspension – it is not meant to carry the entire rated load. We do not recommend that the coil springs be altered from the OEM suspension specification, unless an applicable commercially available suspension kit is fitted.
- ⚠** The kit is designed to suit a standard vehicle configuration – modifications to the vehicle outside the kit design parameters may adversely affect fitment and operation such as:
 - Height changes outside any noted in the kit specification.
 - Larger dampers (Shock Absorbers)
 - Wheel and tyre changes
 - Exhaust changes.
- ⚠** If your vehicle is fitted with a brake proportioning valve or stability control system it is important to ensure this is maintained and adjusted according to the vehicle manufacturer's instructions.
- ⚠** It is recommended that only a properly qualified person installs the product and carries out maintenance. If you are not qualified and attempt to carry out such work ensure that all safety equipment is used and safety standards are met.
- ⚠** Ensure that you have read the full Product Manual before attempting to fit the product.
- ⚠** Ensure the Product Manual is kept with the vehicle and that any vehicle owner and/or operator is fully advised on the system and its operation before attempting to drive or operate it.



SEE OTHER WARNINGS AND IMPORTANT INFORMATION IN THE PRODUCT MANUAL

LHS = LEFT SIDE OF THE VEHICLE WHEN FACING FORWARD

STEP 1 – AIR LINE TUBING & FITTINGS - GENERAL NOTES

CUTTING

Only cut the airline tubing with a sharp blade making the cut as square as possible.

Always trim the tubing before re-inserting into the fitting.

- ⚠** If you use a sharp utility knife or razor blade great care must be taken in all cases not to cut yourself during this operation.

CONNECTING & REMOVING

To connect:

Push the freshly trimmed tubing into the fitting as far as possible.


To remove:

First release the air pressure from the system. To withdraw the tubing, push and hold the collar on the fitting away from the tube and pull out the tubing.

Hint In confined spaces an open ended spanner can be used to evenly depress the collar and remove the airline tubing.

**CUT TUBING
SQUARE WITH
SHARP BLADE
OR TUBE
CUTTER**



**DO NOT USE
PLIERS, SIDE
CUTTERS OR
PIPE CUTTERS**



STEP 2 – POSITION YOUR INFLATION VALVES

Select a convenient location for the air inflation valves such as the bumper or the body of the vehicle. It must be protected from road damage and be accessible for air inflation equipment.

Drill a 5/16" hole and install the air inflation valve using two 5/16" stainless steel washers as supports where required.




STEP 3 - PREPARE THE AIR LINE TUBING

The air line is supplied with split protector tube pre-fitted to shield the air line during and after installation. Decide on a suitable route for the air line from the airbag to the inflation valve location to avoid direct heat from engine, exhaust pipe, and away from sharp edges.

Uncoil the air line tubing being careful not to fold or kink it and cut to length to suit the chosen route. Once routed, the protector tube is pulled back later to prepare the protected air line.

DO NOT CONNECT OR SECURE THE AIR LINE AT THIS POINT



STEP 4 – PREPARE THE VEHICLE ACCORDING TO VEHICLE MAKE

In order to fit this kit the coil springs need to be removed and over-ride bumpers removed for modification. Ensure this operation is carried out according to the vehicle manufacturers instructions.

STEP 5 – MODIFY OVER-RIDE BUMPERS & DRILL BUMPERS AND SPRING SEAT

Cut off the bumper at the first recess from the top, as shown. Remove any excess rubber to make the remaining top section reasonably flat.

Drill out the centre holes of the bumper and spring seat to approximately 19mm diameter, remove any sharp edges.



STEP 6 - RED PLUGS

Use of the red plugs supplied is optional. They will enable a general reduction in airbag size which may be required to ease an airbag into a coil spring which is out of the vehicle, and they will fully flatten an airbag for easy insertion into an in-situ extended coil spring through the winding.

USING RED PLUGS: Flatten the airbag with the airline fitted and plug the other end of the airline tubing with the red plug. The airbag should now remain flattened whilst you perform fitment into the coil spring.




STEP 7 – INSERT AIRBAG INTO COIL SPRING

Insert the airbag into coil spring with the air inlet at the top end of the spring.

STEP 8 – POSITION SUPPORT

Position the protector with the chamfered hole facing the air fitting, as shown.



STEP 9 – CONNECT AIRLINE TUBING AND TEST CONNECTIONS

CONNECT the airline tubing by inserting one end into the airbag air fitting, the other end into the installed inflation valve.

Hint Flat nose pliers may be used to lightly grip the airline tubing to ensure it is fully inserted into the airbag fitting.

INFLATE the airbag to the maximum allowed pressure (see Specific Airbag Operating Pressures) and check for leaks at the connections using soapy water spray. We recommend a soapy water spray solution of 25% soap to 75% water.

DEFLATE the airbag. If no leak, continue. If leak detected, remove the airline tubing, re-cut and re-test.

CHECK airbag is not in contact with any sharp edges or is too close to exhaust heat in all load and height conditions.

STEP 10 – COIL SPRING RE FITMENT

Re-position the coil spring and over-ride bumper on the vehicle whilst feeding the air line tubing through the over-ride bumper/holder and/or spring seat.

Ensure the coil orientation is correct, and the air line tubing does not get kinked during this process, or when during the next step.


STEP 11 – FITMENT COMPLETION

Position the airbag midway down the coil spring and secure the air line tubing in this position so enough slack is left to allow for full suspension movement

Return the vehicle to driving position. Ensure this operation is carried out according to the vehicle manufacturers instructions.


STEP 12 – SETTLING IN OF AIRBAGS

The airbags in this kit are smaller in diameter than the inside of the vehicles coil springs, but they are able to stretch out to fill the coil space.



**BELLOWS LOOSE INSIDE
COIL PRIOR TO INFLATION**

To stretch the airbags, inflate them up to 20 psi (1.4 bar) or higher, if required (but only to the maximum Specific Airbag Operating Pressure below). Leave airbags inflated for at least 2 weeks. The stretching out will allow the airbags to settle into position and provide the best performance in use.



**BELLOWS WILL SETTLE IN
TO SHAPE OF COIL SPRING**

STEP 13 – TO FINISH

Ensure the **WARNING** label is fixed in a prominent position in sight of the vehicle operator.

Ensure the Product Information Wallet is given to the vehicle owner/operator.

Ensure the vehicle owner/operator fully understands how to use the product.

All fixings should be checked for tightness after the first laden run and thereafter as per the original manufacturer's recommendations.

SPECIFIC AIRBAG OPERATING PRESSURES

See operating instructions section for proper use and apply the specific pressures below:

STANDARD KIT ***WITHOUT HP SLEEVES***

MINIMUM
5 PSI (0.4 bar)

MAXIMUM
30 PSI (2 bar)

**DID YOU KNOW WE OFFER HIGH
PRESSURE SLEEVE KITS TO SUIT
OUR COIL-RITE AIRBAGS?**

**WANT TO KNOW MORE ABOUT
HIGH PRESSURE SLEEVE KITS?**

**CALL AIRBAG MAN ON
FREECALL 1800 247 224**

Adjust and maintain pressure up to the stated maximum to level the vehicle for the load imposed and always maintain the minimum airbag pressure.



Failure to do so may result in product or vehicle damage not covered under warranty.

**IF MORE PRESSURE IS REQUIRED TO LEVEL THE VEHICLE
CALL AIRBAG MAN ON 1800 247 224 FOR FURTHER TECHNICAL ADVICE**



FREECALL 1800 247 224



-  Incorrect use of this air suspension product can result in damage to the airbag, associated parts and/or the vehicle, which is not covered under warranty.
-  Ensure the airbags are maintained at the stated ride height at all times and the maximum pressure is never exceeded.